60CM PYROLYTIC OVEN w TFT screen – BOP7568LX



SPECIFICATIONS

- Multifunction + Oven
- Smart Assist function
- Boost function
- 3 Pyrolytic cleaning cycles 2hr, 1:30hr, *Clean 39*′
 - At each end of cooking, "Clean 39" flashes on the screen offering you to start this cleaning. Go to the cleaning menu and validate "Clean 39".

 To start *Clean 39'* cycle, oven must have enough residual heat, if not, this function is not applicable. 0:00 will appear on the screen, then you will need to choose one of the other cleaning functions.
- Volume: 73L
- 6 shelf levels + self adjustable telescopic railing
- Electronic touch control with TFT full color LCD display
- Soft close
- 8 cooking functions + 12 Flavor guide dishes + 15 <u>Auto cook dishes</u> + Steam cooking
 - Auto cook A selection of 12 dishes for 100% automated cooking.
 - Select the dish category, insert your food item.
 - The oven self-programmes the suitable cooking function, temperature and time for a perfect cook, every time.
- Enamel cavity
- Interior halogen lighting
- Accessories: 1 x 45mm drip tray
 - 1 x 20mm drip tray
 - 1 x safety grid / 1 x self adjustable telescopic railings





60CM PYROLYTIC OVEN w TFT screen – BOP7568LX



Steam Cooking



Brandt offers you 3 new functions which automatically combine two cooking methods:

Traditional cooking + Steaming

In order to preserve the nutritional qualities of foods and achieve faster cooking.



WHITE MEAT

Recommended for preserving the softness and tender character of roast pork and veal.



FISH

Recommended for cooking whole fish or fillets.



POULTRY

Recommended for cooking chickens, turkeys, guinea fowl and ducks.

For combi-steam function, all you need is 2 simple steps:

- 1.Add sufficient lukewarm water to your drip pan and place it in your oven on the bottom shelf.
- 2.Place your food on level 3.

**For the quantity of water to be placed in the drip pan, refer to the table of automatic combined functions with combination of steam at the end of the user manual.

60CM PYROLYTIC OVEN w TFT screen – BOP7568LX



ELECTRICAL CONNECTIONS

- Maximum electric power (W): 3385
- Current (A): 15
- Voltage (V): 220 -240
- Frequency (Hz): 50 / 60
- Length of electrical supply cord (cm): 115
- Type of plug: Without

DIMENSIONS

- Dimension of product (mm): H596 x W592 x D544
- Built in dimensions (mm): $H585 \times W560 \times > D545$
- Net weight (kg): 36.8
- Gross weight (kg): 38.1

60CM PYROLYTIC OVEN w TFT screen — BOP7568LX



INSTALLATION DIAGRAM







